

| COCKPIT PREPARATION | | Dash8 |
|--|---------------|-------|
| | | Q400 |
| Color Coding: NORMAL APU STARTUP PROCEDURE | November 2017 | |

BEFORE FIRST FLIGHT OF THE DAY (PNF)

| EXTERNAL WALK AROUND BY PF | COMPLETED |
|----------------------------|------------------|
| BATTERY SWITCHES | ALLON |
| DC GENS | ON |
| EXTERNAL POWER | AS REQUIRED |
| COCKPIT LIGHTS | AS REQUIRED |
| ALL SCREENS | ON |
| APU CIRCUIT BREAKER | IN |
| APU POWER | ON |
| APU FIRE TEST | TESTED |
| APU START | PRESS |
| APU GENERATOR / LOADING | ONLINE / CHECKED |
| DOCUMENTATION | ONBOARD |
| MASKS OXYGEN x3 | CHECK GREEN |
| GEAR PINS | IN SITU x3 |
| SMOKE HOOD | IN SITU |
| TORCHES | IN SITU x2 |
| CRASH AXE | IN SITU |
| FIRE EXTINGUISHER | IN SITU |
| FIRE GLOVES | IN SITU |
| SMOKE GOGGLES | IN SITU |

BEFORE FIRST FLIGHT OF THE DAY (CPT)

| CIRCUIT BREAKERS | IN |
|---------------------------|-----------|
| TAKEOFF WARNING TEST HORN | TESTED |
| ADC | TESTED x2 |
| STALL COMPUTERS | TESTED x2 |

BEFORE FIRST FLIGHT OF THE DAY (F/O)

| CIRCUIT BREAKERS | IN |
|-------------------|-----------|
| OXYGEN LEVEL | IN LIMITS |
| FWD OUTFLOW VALVE | CLOSED |

BEFORE FIRST FLIGHT OF THE DAY (PNF)

OVERHEAD CHECKS

| OVERHEAD CHECKS | | |
|--------------------------------|---------------------|--|
| BATTERIES | ALL ON | |
| MAIN BUS TIE | TIE | |
| DC GENS | ON | |
| EXTERNAL POWER | AS REQUIRED | |
| DEICE BOOTS SELECTORS | OFF | |
| PROP TEST | OFF | |
| ICE PROTECTION INTAKE DOORS | OPEN | |
| REF SWITCH (ED INDICATION) | TESTED / OFF | |
| BOOT AIR SWITCH | NORMAL | |
| PITOT STATIC SWITCH | OFF | |
| WINDSHIELD HEAT | OFF | |
| WINDSHIELD WIPERS | OFF | |
| PILOT SIDE WINDOW HEAT | OFF | |
| ALL EXTERNAL LIGHTS | OFF | |
| PRESS COMPUTER INDICATORS | CHECKED | |
| FDR | TESTED | |
| FIRE DETECT LEFT / RIGHT, C/Ls | TESTED x2 | |
| BAGGAGE SMOKE DETECTOR | TESTED x2 | |
| PANEL LIGHTS | TESTED, AS REQUIRED | |
| STORM / DOME LIGHTS | TESTED, AS REQUIRED | |
| APU BLEED | AS REQUIRED | |
| IGNITIONS | NORMAL x2 | |
| START SELECT SWITCH | CENTERED | |
| START / SELECT LIGHTS | OUT | |
| CABIN ALTITUDE | SET | |
| PRESSURIZATION MODE | AUTO | |
| FWD OUTFLOW VALVE | CLOSED | |
| EXTERNAL LIGHTS | AS REQUIRED | |
| EMERGENCY LIGHTS | TESTED & ARMED | |
| NO SMOKING SIGNS | TESTED / ON | |



COCKPIT PREPARATION

Dash8 **Q400**

Color Coding: NORMAL APU STARTUP PROCEDURE

November 2017

BEFORE FIRST FLIGHT OF THE DAY (PNF)

OVERHEAD CHECKS (CONT)

| SEAT BELT SIGNS | TESTED, AS REQUIRED |
|--------------------------|---------------------|
| DIM / BRIGHT SWITCH | TESTED, AS REQUIRED |
| CAUTION / WARNING LIGHTS | TESTED |
| TEMPERATURE CONTROLS | 12 O'CLOCK |
| AIR CONDITION PACKS | AUTO |
| BLEED AIR | MIN / OFF |
| RECIRC FAN | ON |
| AC GENERATORS SW | ON x2 |
| AC EXTERNAL POWER SW | OFF |
| | |

BEFORE FIRST FLIGHT OF THE DAY (PNF)

GLARESHIELD AND BELOW CHECKS

| FLIGHT / TAXI SWITCH | TAXI |
|---|--------------------|
| CAP / FO ND TO TERR, GPWS TEST | TESTED |
| ANTI SKID | TESTED |
| GEAR WARNING HORN | TESTED |
| AUTOFEATHER PRESS IN, OFF AFTER TEST COMPLETED | TEST PASSED |
| STBY COM ON, | VERIFY "STBY CTRL" |
| OFF AFTER TEST COMPLETED | ON ARCDU |
| COCKPIT VOICE RECORDER | TESTED |
| TRIMS, RUDDER, ELEVATOR, AILERONS | FULL & FREE |
| POWER LEVERS | DISC |
| CONDITION LEVERS | FUEL OFF |
| ARCDU - TCAS | TESTED |
| AVIONICS | TESTED |

| TECHNICAL REPORT |
|------------------|
|------------------|

NOTE ANY FAULTS



NORMAL CHECKLIST

Dash8 **Q400**

Color Coding: NORMAL FIRST FLIGHT OF THE DAY CHALLENGE AND RESPONSE

November 2017

FLIGHT DECK SAFETY CHECKS (PNF)

| DOCUMENTATION | ONBOARD |
|---|----------------|
| BATTERIES | ON & CHECKD |
| MAIN BUSTIE | TIE |
| DC EXTERNAL POWER/APU | ON |
| BATTERY TEMPS | CHECKED |
| BUS VOLTAGES | CHECKED |
| SAFETY EQUIPMENT: SMOKE GOOGLES, FIRE GLOVES, CRASH EXE, TORCHES, SMOKE HOOD, ESCAPE ROPE, LIFE VESTS, FIRE EXTINGUISHERS | CHECKED |
| LDG GEAR LIGHTS | CHECKED 3 |
| ENGINE INTAKE DOORS | GREEN |
| CIRCUIT BREAKERS | CHECKED IN |
| ALT GEAR DOOR, INHIBIT SWITCH | NORM |
| FIRE AND SMOKE DETECTION | TESTED |
| BLEED AIR 1 & 2 | OFF |
| APU BLEEDS | AS REQUIRED |
| RECIRC FAN | ON |
| PRESSURIZATION | SET & CHECKED |
| A/C PACKS | CHECKED |
| EMERGENCY LIGHTS | ARM |
| FUEL TRANSFER, QUANTITY | OFF,L/R |
| PARKING BRAKE, PRESSURE | ON & CHECKED |
| POWER AND CONDITION LEVERS | DISC, FUEL OFF |
| NOSE STEERING | OFF |
| FMS | SET |
| T/O AND DEPARTURE BRIEFING | COMPLETED |

BEFORE START (F/O)

| TRIMS | SET x3 |
|-------------------------|-----------------------------------|
| DOOR AND FUELING LIGHTS | OUT |
| PASSENGER SIGNS | ON |
| CABIN REPORT | RECEIVED |
| FLIGHT DECK DOOR | LOCKED |
| A/COL LIGHTS | RED |
| APU BLEED | OFF |
| BATTERIES, BUS VOLTS | ON > 26V; FOR BATT START > 22V |

AFTER START (F/O)

| EXT POWER / APU | DISCONN. / OFF |
|-------------------|------------------|
| MAIN BUS TIE | OFF |
| ELECTRICAL PANELS | CHECKED |
| COND. LEVERS | MAX |
| AUTOFEATHER | SELECTED / WHITE |
| FUEL PUMPS | ON |
| HYDRAULICS | CHECKED |
| FLAPS & SPEEDS | XCHECK & TABLE |
| RUDDER | FULL TRAVEL |
| NOSE STEERING | ON |
| PFD MFD ED | CHECKED |
| BLEEDS | ON / MIN |
| DE-ICE PRESSURE | CHECKED |
| ICE PROTECTION | TEST / SET |
| XPDR, TCAS | ALT, ON |
| | |

TAXI (F/O)

| BRAKES | CHECKED |
|--|----------------|
| TAKEOFF WARNING | TESTED |
| TAKEOFF POWER | NTOP OR RDC % |
| FLIGHT INSTRUMENTS | CHECKED |
| #3 HYD PUMP ON, ELEVATOR AND AILERONS FULL TRAVEL, #3 HYD PUMP OFF | FULLTRAVEL |
| YAW DAMPER | ON |
| CLEARANCES | REVIEWED BY PF |
| CABIN | SECURED |

LINE UP (F/O)

| A/COL LIGHTS | WHITE |
|-----------------------------|---------------|
| LANDING LIGHTS | ON |
| PITOT/STATIC ISOL VALVE | ON |
| BLEEDS | AS REQUIRED |
| AFCS MODES: GA, HDG, ALTSEL | SET & CHECKED |
| CAUTION PANEL | BLACK |

AFTER TAKEOFF (PNF)

| LANDING GEAR | UP |
|--------------|---------|
| FLAPS | ZERO |
| BLEEDS | ON/NORM |
| CLIMB POWER | SET |



| NORMAL CHECKLIST | Dash8 |
|------------------|-------------|
| | Q400 |

Color Coding: NORMAL FIRST FLIGHT OF THE DAY CHALLENGE AND RESPONSE

November 2017

CLIMB (PNF)

| 1013/29.92 |
|-------------|
| AS REQUIRED |
| CHECKED |
| NORM |
| OFF |
| OFF |
| |

DESCENT (PNF)

| PRESSURIZATION | SET |
|-------------------------------|-------------|
| GPWS FLAPS | AS REQUIRED |
| BRIEFING, MSA, SPEEDS, DH/MDA | TABLE / SET |

APPROACH (PNF)

| ALTIMETERS | QNH SET |
|-----------------|---------|
| FUELTRANSFER | OFF |
| FUEL PUMPS | ON |
| STBY HYD, PTU | ON |
| HYDRAULICS | CHECKED |
| PASSENGER SIGNS | ON |
| CAUTION PANEL | BLACK |
| CABIN | SECURED |

LANDING (PNF)

| ICE PROTECTION | AS REQUIRED |
|------------------|-------------------|
| LANDING GEAR | DOWN 3 GREENS |
| CONDITION LEVERS | MAX |
| FLAPS | SET / INDICATING |
| BLEEDS | MIN / AS REQUIRED |

AFTER LANDING (F/O)

| CONTROL LOCK | ON |
|----------------|------|
| A/COL LIGHTS | RED |
| FLAPS | ZERO |
| WEATHER RADAR | STBY |
| FUEL PUMPS | OFF |
| FLIGHT / TAXI | TAXI |
| ICE PROTECTION | OFF |
| MAIN BUSTIE | TIE |
| YAW DAMPER | OFF |

SHUTDOWN (F/O)

| PARK BRAKE | ON |
|-------------------------------|------------------------|
| HYD PUMP / PTU | NORM |
| POWER AND CONDITION LEVERS | DISC / START & FEATHER |
| NOSE STEERING | OFF |
| WXR | OFF |
| XPDR / TCAS | STBY |
| BLEEDS | MIN / OFF |
| GPU / APU | AS REQUIRED |
| COND. LEVERS (AFTER 30s) | FUEL OFF |
| PASSENGER SIGNS | OFF |
| LIGHTS | AS REQUIRED |
| BATTERY MASTER | AS REQD (ON & APU) |

LEAVING AIRCRAFT (F/O)

| ICE PROTECTION / INTAKE DOORS | OFF / CLOSED |
|-------------------------------|--------------|
| RECIRC FAN | OFF |
| IGNITIONS | OFF |
| APU | OFF |
| EMERGENCY LIGHTS | OFF |
| ANTI-SKID | OFF |
| BATTERIES & BATT MASTER | OFF |
| DOME & BOARDING LIGHTS | OFF |

When flying in icing conditions, add 20 kts to VAPP, VREF, VGA for flaps 10°, 15° and 35°.

FLAP RETRACTION INITIATION SPEED (VFRI) FINAL TAKEOOF SPEED (V SCLIMB)

| WEIGHT | V FRI FLAP 5° | V FRI FLAP 10° | V FRI FLAP 15° | V CLIMB |
|-----------|---------------------|----------------------|----------------------|------------|
| 18.000 KG | 116 | 110 | 107 | 130 |
| 20.000 KG | 120 | 112 | 109 | 131 |
| 22.000 KG | 126 | 118 | 115 | 137 |
| 24.000 KG | 132 | 123 | 120 | 143 |
| 26.000 KG | 137 | 128 | 125 | 148 |
| 28.000 KG | 142 | 134 | 130 | 154 |
| 29.000 KG | 146 | 137 | 133 | 158 |